

Suitable for Transferring Kerosene & Diesel

- 10 minutes to empty 200 L drum.
- Easy to use gun nozzle.
- Suction pipe with mesh strainer.

■ Applications

- Kerosene
- Diesel



■ Specifications

Model	FP-25	FP-2512
Connection Dia	25 mm (1")	
Total Head	3.5 m (11 ft)	2.8 m (9 ft)
Delivery Volume	20 L/min (5.3 USG/min)	18 L/min (4.7 USG/min)
Voltage	AC 100 V AC 220 V	DC 12 V
Frequency	50 Hz / 60 Hz	
Power Code	4 m (13 ft)	
Delivery Hose	1.5 m (4.9 ft)	
Gross Weight	3.8 kg (8.3 lbs)	3.1 kg (6.8 lbs)
Dimensions LxWxH (mm)	1190 × 235 × 130	
Packing Unit	1	



FP-25

For High Viscosity Oil (Up to 2000 cst)

- Specially designed for dispensing oil at service stations.



SO-25

■ Applications

- High viscosity oil



"HIGH LITER PUMP" High Volume

- Delivers 1 L per rotation.
- Mesh strainer can filter fine dust.
- Applicable for low viscosity oil.



LP-32

■ Applications

- Diesel
 - Kerosene,
 - Heavy fuel oil A
- *Oil temperature is over 10°C



■ Specifications

Model	SO-25
Delivery Volume	0.5 L/Stroke (0.1 USG/Stroke)
Pump Length	1380 mm (54")
Suction Pipe Dia	32 × 1038 (1¼" × 40")
Gross Weight	55 kg (121.2 lbs)
Dimensions LxWxH (mm)	1080 × 398 × 220
Packing Unit	5

■ Specifications

Model	LP-32
Delivery Volume	1 L / 1 Rotation, (Normal Use) 100 L/min (26 USG/min)
Suction Pipe	32 × 956 (1¼" × 37")
Delivery Hose (mm)	32 × 1280 (1¼" × 50")
Strainer	#60 with Mesh, Polyethylene
Gross Weight	38 kg (83.7 lbs)
Dimensions LxWxH (mm)	1137 × 252 × 295
Packing Unit	5